

LDH49-SAI200 49" Wall-mounted LCD Digital Signage



Features :

· Industrial design, support video, picture, text, audio and other multimedia information released, made for advertising industry

· Support remote timing switch function, can be customized holidays, spring, winter and other different dates, different time of the timer switch function

· Support cycle play, specified time play, inter-cut, interval play and so on

· Support multi-level permission settings and management, unaudited programs can not be added to the schedule and play at the terminal

· Support remote screen capture function, look over the current play state of the terminal

· Support the program material off the network or outage resume function, greatly save bandwidth and network flux

1080p 24h* Wi Fi

Model	LDH49-SAI200	Uplink N
Panel Size	49" TFT LCD	Downlin
Display Ratio	16:9	Interfa
Maximum Resolution	1920×1080	Ethernet
Display Color	16.7M	USB
Brightness (nits)	400cd/m ²	
Contrast	1200:1	SD
Viewing Angle	178°/178°	SIM
Response Time	8ms	Other
Backlight	LED	Dimensi
Performance		Net Wei
System	Android4.4	Material
•		Protecti
RAM	1GB	Protecti
Internal Storage	8GB	Installat
Decoding Ability	3CH 1080P@60fps	Display I
Ntework Mode	Wired, Wi-Fi, 3G/4G(optional)	Power
Built in Loudspeaker	2W+2W	Standard

Uplink Network	Ethernet port, Wi-Fi	
Downlink Network	Wi-Fi hotspot	
Interface		
Ethernet	1 RJ45	
USB	2 USB2.0	
SD	1	
SIM	1(optional, for 3G/4G module)	
Others		
Dimension	1138.8×674.2×85.2 (mm)	
Net Weight	37kg	
Material	Aluminum frame and metals rear cover	
Protective cover	6mm stalinite	
Protection	IP50	
Installation Mode	Wall-mouted	
Display Mode	Horizontal, vertical	
Power	AC100-240V, 50/60Hz	
Standard Consumption	70W	

Technical Specification

Specification

LDH49-SAI200

Work Environmet

Temperature: -10[°]C~+55[°]C Humidity: 10%~90%

Dimensions(mm)





